

CERTIFICATE OF COMPLIANCE

Certificate Number E256367
Report Reference E256367-20060105
Issue Date 2020-JUNE-18

Issued to: CMP Products Ltd
Glasshouse St, St Peters
Newcastle-Upon-Tyne, NE6 1BS UNITED KINGDOM

**This certificate confirms that
representative samples of**

CABLE FITTINGS FOR USE IN ZONE CLASSIFIED
HAZARDOUS LOCATIONS
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 2225 STANDARD FOR CABLES AND CABLE-
FITTINGS FOR USE IN HAZARDOUS (CLASSIFIED)
LOCATIONS
UL 60079-0 EXPLOSIVE ATMOSPHERES - PART 0:
EQUIPMENT - GENERAL REQUIREMENTS
UL 60079-7 EXPLOSIVE ATMOSPHERES - PART 7:
EQUIPMENT PROTECTION BY INCREASED SAFETY 'E'
UL 514B – Standard for Conduit, Tubing and Cable Fittings

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E256367
Report Reference E256367-20060105
Issue Date 2020-JUNE-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL Cat. No. T3CDS, **T3CDSX**, may be followed by HT, provided with Prefix -16, -20S16, -20S, -20, -25S, -25, -32, -40, -50S, -50, -63S, -63, -75S, -75 or -90. For use in Class I, Zone 1, AEx e II Hazardous Areas. For use with marine shipboard cable employing copper, bronze, aluminum or stainless steel grounding braid. Thread sizes ½ to 3 in. NPT and M16 to M90 inclusive.

	Trade Size		Max. Diameter Over Marine Shipboard Braided Sheath		Jacket Diameter	
					In.	mm
Cat. Nos. T3CDS, T3CDSX	Ft/in.	Metric	In.	mm	Min/Max	Min/Max
16	1/2	M16	0.25	6.4	0.28/0.53	7.0/13.4
20S16	1/2	M20	0.25	6.4	0.28/0.53	7.0/13.4
20S	1/2	M20	0.40	10.2	0.37/0.63	9.5/15.9
20	1/2	M20	0.43	11.0	0.49/0.82	12.5/20.9
25	3/4	M25	0.63	16.1	0.67/1.03	17.0/26.2
25S	3/4	M25	0.63	16.1	0.55/0.87	14.0/22.0
32	1	M32	0.69	17.6	0.90/1.33	22.9/33.9
40	1-1/4	M40	0.93	23.7	1.02/1.59	26.0/40.4
50S	1-1/2	M50	1.48	37.7	1.46/1.74	38.0/46.7
50	2	M50	1.48	37.7	1.49/2.09	38.0/53.1
63S	2	M63	1.48	37.7	1.80/2.34	45.6/59.4
63	2-1/2	M63	1.89	48.0	2.15/2.60	54.6/65.9
75S	2-1/2	M75	1.89	48.0	2.28/2.84	58.0/72.1
75	3	M75	2.26	57.4	2.38/3.09	60.4/78.5
90	3	M90	2.79	70.9	2.72/3.56	69.2/90.4



Bruce Mahrenholz, Director North American Certification Program
 UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

